RTC-8050 Series II

50-ton (45.36 mt) Rough Terrain Telescopic Boom Crane

3

- 50-ton (45.36 mt) at 10 ft (3.05 m) radius
- 110 ft (33.5 m) full-power, four-section boom with quick-reeve boom head
- 168 ft (51.2 m) maximum tip height
- 51 ft (15.5 m) two-piece (bi-fold) fly, stowable, offsettable to 2°, 20° and 40° -Optional
- No deducts for stowed attachments
- A-max boom mode
- MG-434 rated capacity limiter
- Flat deck design with full length fenders
- 185 hp (138.0kW) Cummins engine
- Direct mounted electronic transmission
- Hydro-gas ride™ suspension
- Pilot-operated hydraulic controls

RTC-8040 *Series II* 40-ton (36.29 mt) Rough Terrain Telescopic Boom Crane

The RTC-8040 Series II boasts all of the outstanding features of the RTC-8050 Series II, the exceptions are:

- 40-ton *(36.29 mt)* at 10 ft *(3.05 m)* radius
- 110 ft (33.0 m) full-power, four-section boom with quick-reeve boom head
- 163 ft (49.7 m) maximum tip height
- 165 hp *(123.0kW)* Cummins engine



RTC-8050

Series II Rough Terrain Telescopic Boom Crane 50-ton (45.36 mt)

RTC-8040

Series II Rough Terrain Telescopic Boom Crane 40-ton *(36.29 mt)*



Lightweight nylon head sheaves (including the optional auxiliary lifting sheave shown here) reduce overall machine weight and increase lift capacities.

Quick reeve boom head allows rope to be easily reeved over boom head.

The exclusive "A-Max" system provides optimum strength and stability. For in-close, big picks, the "A-Max" mode allows the operator to extend only the inner midsection of the boom.

Hammerhead boom nose allows the operator to work at high boom angles.

Type "RB" 18x19 wire rope is standard

> Mechanical boom angle indicator standard

The "Boss" is Link-Belt's patented boom design of high-strength angle cords and high formability sidewall embossments.

The Confined Area Lifting Capacities (CALC) system provides three outrigger positions: • full retraction • intermediate

extension • full extension Deep front storage box

Optional 51' (15.54 m) two-piece (bi-fold) lattice fly, stowable, offsettable to 2°, 20° and 40°

> Non-slip surface strips on carrier deck

CONSTRUCTION EQUIPMENT

Integrated steps and hand-holds within the sheet metal

Folding steps for transport



Smooth ride... **4-Link suspension**

The fully independent rear 4-Link suspension greatly reduces the inherent bouncing at medium speeds and greatly improves handling, maneuverability and turning radius in both on- and off-road conditions. To further reduce the bounce, the exclusive Hydro-gas™ Ride system serves as a shock absorber through a charged accumulator system for greatly improved carrier stability.



Access is the name of the game

Fold-up steps and hand rails at six

carrier's deck provide the ultimate in

machine access.

points and non-slip surface strips on the





Operators-Cab...

Roomier and more ergonomic than traditional cabs, the Cab features include:

- Larger window openings for increased operator visibility
- · Tilt-telescopic steering column now includes controls and switches for excellent operator control and comfort
- · Six-way adjustable fabric seat with lift-up armrest (which deactivates control functions when raised)
- · Armrest mounted, responsive dual axis hydraulic controllers
 - Bubble level sight level mounted on console
 - · Single foot pedal control
 - Ducted air through automotive-style directional vents
 - Sliding right side, rear • windows and swing-up roof window
 - · Corner-post-mounted, backlit gauges
 - Dashless design
 - · Large, sweeping electric wipers

Standard load hoist system consists of a main winch with two-speed motor and automatic brake for power up/down mode of operation.

A bi-directional hydraulic motor, driven through a planetary reduction unit provides precise smooth load control with minimal rpm's.

Asynchronous, parallel double-over grooved drums minimize rope harmonic motion, improving spooling and increasing rope service life. A two-speed auxiliary winch is an available option.





Four modes of steering: Independent front

- Coordinated four wheel
- Four wheel "crab"

. use of . Independent rear

" beams

itrols

Link-Belt's innovative two-part paint coating technology, coupled with a pre-assembly paint process, provides the finest quality coating system available today. Paint chipping, cracking and deterioration is significantly reduced when service work and disassembly are required.



With your Link-Belt distributor, your crane investment is always protected.

When you invest in a Link-Belt crane, you invest in a 125-year legacy of outstanding customer



support through a worldwide Link-Belt distribution network. The value of a machine starts with state-of-the-art design and quality manufacturing, but excellent product support greatly impacts the fact that Link-Belt cranes traditionally command some of the highest resale prices in the industry.





The right people with the right part at the right time.

Highly trained crane technical specialists get to the core issues quickly to get you going again.

Through the Master Technician Training Program, technicians are specifically tested to establish proficiency in all phases of machine

> diagnostics and repair. At our Service Training Center, schools are held throughout the spring and fall for both distributor technicians and customers.

Supporting these trained distributor personnel, experienced factory advisors with comprehensive machine records, CAD computer terminals, and technical electronic publication libraries stand ready to isolate facts and quickly act to resolve crane service issues.

With eParts, our online computer system, distributors worldwide can order Genuine Link-Belt Parts 24 hours a day, seven days a week. Our dedicated 72,000 sq. ft. Parts Distribution Center is an integral part of Link-Belt's product support where all parts in stock ship the same business day.

Iink-Belt is a registered trademark. Copyright 2002. All rights reserved. We are constantly improving our products and therefore reserve the right to change designs and specifications.

Litho in U.S.A. 2/05 #4301 (supersedes #4266)

Link-Belt Construction Equipment Company is a leader in the design, manufacture and sales of telescopic and lattice boom cranes, with headquarters in Lexington, Kentucky.

In the recent decade, a dynamic and highly focused Link-Belt has emerged as a market leader in crane design and product quality standards by focusing on continuous improvement and employee empowerment.

Link-Belt operates on the principles of continuous quality improvement, ISO 9001, and established values that support the vision of quality. These principles result in reduction in waste, better use of company resources and improved employee and customer satisfaction.

With major capital improvements over the last ten years, along with continuous improvement philosophies, this facility has emerged as the most modern crane facility in North America.

CONSTRUCTION EQUIPMENT Lexington, Kentucky www.linkbelt.com



Technical Data

Specifications & Capacities





CAUTION: This material is supplied for reference use only. Operator must refer to in-cab Crane Rating Manual and Operator's Manual to determine allowable crane lifting capacities and assembly and operating procedures.

5472 (supersedes 5427)-0506-J6

Table Of Contents

Boom, Attachments, and Upper Structure	1
Boom	1
Boom Head	1
Boom Elevation	1
Auxiliary Lifting Sheave – Optional	1
Hook Blocks and Balls – Optional	1
Fly – Optional	1
Operator's Cab and Controls	1
Swing	2
Electrical	2
Load Hoist System	3
Load Hoist Performance	3
2M Main and Optional Auxiliary Winches	3
Hydraulic System	3
Counterweight	3
Carrier	4
General	4
Outriggers	4
Steering and Axles	4
	4
Tires and Wheels	4
	4
	4
	4
	4
Carrier Speeds and Gradeability	5
Fuel Iank	5
	5
	5
Axie Loads	6
General Dimensions	7
Working Range Diagram	8
Boom Extend Modes	9
Main Boom Lift Capacity Charts – Standard	10
Fully Extended Outriggers – 360° Rotation	10
On Tires – Stationary – Boom Centered Over Front Between Tire Tracks	11
On Tires – Pick & Carry (Creep) – Boom Centered Over Front	11
On Tires – Stationary – 360° Rotation	11
Fly Attachment Lift Capacity Charts – Optional	12
Fully Extended Outriggers – 360° Rotation	12
110 ft Main Boom Length – 2° Fly Offset	12
110 ft Main Boom Length – 20° Fly Offset	12
110 ft Main Boom Length – 40° Fly Offset	12

Main Boom Lift Capacity Charts – Optional (Metric)	13
Fully Extended Outriggers – 360° Rotation	13
On Tires – Stationary – Boom Centered Over Front Between Tire Tracks	14
On Tires – Pick & Carry (Creep) – Boom Centered Over Front	14
On Tires – Stationary – 360° Rotation	15
Fly Attachment Lift Capacity Charts – Optional (Metric)	15
Fully Extended Outriggers – 360° Rotation	15
33.53m Main Boom Length – 2° Fly Offset	15
33.53m Main Boom Length – 20° Fly Offset	15
33.53m Main Boom Length – 40° Fly Offset	15

Boom, Attachments, and Upper Structure

Boom

Design – Four section, box type construction of high tensile steel consisting of one base section and three telescoping sections. The vertical side plates have diamond shaped steel impressions for superior strength to weight ration. The first telescoping section extends independently by means of one double–acting, single stage hydraulic cylinder with integrated holding valves. The second and third telescoping sections extend proportionally by means of one double–acting, single stage cylinder with integrated holding valves and cables.

Boom

- 35 ft 6 in 110 ft (10.8 33.5m) four section full power boom
- Two mode boom extension: *A*-max mode provides superior capacities by extending the first telescoping section to 60 ft 4 in (*18.4m*). Standard mode synchronizes all the telescoping sections proportionally to 110 ft (*33.5m*). Controlled from the operator's cab.
- Mechanical boom angle indicator
- Maximum tip height for *A*-max mode is 70 ft (21.3m) and standard mode is 118 ft 5 in (36.1m).

Boom Head

- Four 16.5 in (41.9cm) root diameter nylon sheaves to handle up to eight parts of line
- · Easily removable wire rope guards
- Rope dead end lugs on each side of the boom head
 Boom head is designed for quick-reeve of the hook block

Boom Elevation

- One double acting hydraulic cylinder with integral holding valve
- Boom elevation: -3° to 78°

Auxiliary Lifting Sheave – Optional

- Single 16.5 in (41.9m) root diameter nylon sheave
- Easily removable wire rope guards
- Does not affect erection of the fly or use of the main head sheaves

Hook Blocks and Balls – Optional

- 40 ton (*36.3mt*) 4 sheave quick-reeve hook block with safety latch
- 60 ton (54.4mt) 4 sheave quick-reeve hook block with safety latch
- 8.5 ton (7.7*mt*) swivel and non-swivel hook balls with safety latch

Fly – Optional

• 28 ft 6 in (8.7m) one piece lattice fly, stowable, offsettable to 2°, 20°, and 40°. Maximum tip height is 146 ft (44.5m).

28 ft 6 in -51 ft (8.7-15.5m) two piece bi-fold lattice fly, stowable, offsettable to 2°, 20°, and 40°. Maximum tip height is 168 ft (51.2m).

Operator's Cab and Controls

Environmental Cab – Fully enclosed, one person cab of galvaneal steel structure with acoustical insulation. Equipped with:

- Tinted and tempered glass windows
- Extra-large fixed front window with windshield wiper and washer
- Swing up roof window with windshield wiper
- Sliding left side door with large fixed window
- Sliding rear and right side windows for ventilation
- Six way adjustable, cushioned seat with seat belt and storage compartment
- Engine dependent warm-water heater with air ducts for front windshield defroster and cab floor
- · Defroster fan for the front window
- Bubble level
- Circulating fan
- Adjustable sun visor
- Dome light
- Cup holder
- Fire extinguisher
- Left side viewing mirror
- Two position travel swing lock

Air Conditioning – Optional – Integral with cab heating system utilizing the same ventilation outlets

Steering Column – Pedestal type with tilt and telescope functions for operator comfort. Column includes the following controls and indicators:

- Left and right levers include:
- Horn button
- Turn signal switch
- Driving light switch
- Transmission direction switch Panel mounted switches for:
- Travel park brake
 - Steer mode selector
 - 4 wheel drive
 - Transmission gear selector
 - Ether start
 - Hazard flasher
 - Panel mounted indicator/warning lights for:
 - Transmission display
 - Transmission temperature
 - Engine oil pressure
 - Travel park brake
 - Service brake
 - Turn signals
 - Rear wheel offset-optional
 - Emergency steer optional

Armrest Controls - Two dual axis hydraulic joystick controllers or optional single axis hydraulic controllers for:

- Swina
- Boom hoist
- Main rear winch
- Auxiliary front winch optional
- Drum rotation indication
- Drum rotation indicator activation switch
- Winch high/low speed and disable switch(es)
- Third wrap selector switch optional
- Telescopic override switches
- Warning horn button
- Swing park brake

Outrigger Controls - Hand held control box with umbilical cord gives the operator the freedom to view operation while setting the outriggers.

Foot Controls

- Boom telescope
- Swing brake
- Engine throttle

Right Front Console - Controls and indicators for: Bubble level

- Engine ignition
- Engine throttle lock
- Function disable
- Front windshield wiper and washer
- Air conditioning optional Boom floodlight – optional

• 12 volt power connection

- Cab floodlights
- Rotating beacon/Strobe light - optional
- Warning horn
- Third wrap indicator optional
- Heating controls Console dimmer switch

Cab Instrumentation – Ergonomically positioned, analog instrumentation for crane operation including:

- · Engine coolant temperature with warning indicator
- Hydraulic oil temperature with warning indicator
- Fuel level with warning indicator
- Tachometer

Rated Capacity Limiter - Microguard 434 graphic audiovisual warning system integrated into the dash with antitwo block and function limiter. Operating data available includes:

Crane configuration

- Boom length and angle
- Boom head height
- Allowed load and % of allowed load
- Boom angle
- · Radius of load
- Actual load
- Operator settable alarms (include):
 - Maximum and minimum boom angles
 - · Maximum tip height
 - Maximum boom length
 - · Swing left/right positions
 - Operator defined area (imaginary plane)

Internal RCL Light Bar - Optional - Visually informs the operator when crane is approaching maximum load capacity with a series of green, yellow, and red lights.

External RCL Light Bar - Optional - Visually informs the ground crew when crane is approaching maximum load capacity with a series of green, yellow, and red lights.

Swing

Motor/Planetary - Bi-directional hydraulic swing motor mounted to a planetary reducer for 360° continuous smooth swing at 2.5 rpm.

Swing Park Brake – 360°, electric over hydraulic, (spring applied/hydraulic released) multi-disc brake mounted on the speed reducer. Operated by a switch from the operator's cab.

Swing Brake – 360°, foot operated, hydraulic applied disc brake mounted to the speed reducer.

Swing Lock – Two-position swing lock (boom over front or rear) operated from the operator's cab.

360° Positive Swing Lock – Optional – Meets New York City requirement.

Electrical

Swing Alarm - Audio warning device signals when the upper is swinging.

Lights

RTC-8050 II

- Two working lights on front of the cab
- One rotating amber beacon on top of the cab optional
- One amber strobe beacon on top of the cab optional
- Boom floodlight optional

Load Hoist System Load Hoist Performance

Main (Rear) and Auxiliary (Front) Winches – 3/4 in (19mm) Rope											
	Maximum	Line Pull	Normal Line Speed		High Line Speed		Layer		Total		
Layer	lb	kg	ft/min	m/min	ft/min	m/min	ft	m	ft	m	
1	15,390	6 980.8	168	51.2	337	102.7	114	34.7	114	34.7	
2	14,150	6 418.3	183	55.8	366	111.6	124	37.8	238	72.5	
3	13,094	5 939.3	198	60.4	396	120.7	134	40.8	372	113.4	
4	12,185	5 527.0	212	64.6	425	129.5	144	43.9	516	157.3	
5	11,394	5 168.2	227	69.2	455	138.7	154	46.9	670	204.2	

Wire Rope Application		Dian	neter	Туре	Maxi Permissi	mum ble Load
		in	mm		lb	kg
Main (Rear)	Standard	3/4	19	18x19 rotation resistant – right regular lay (Type RB)	12,920	5 860.5
Winch Optio		3/4	19	36x7 rotation resistant – right regular lay (Type ZB)	15,600	7 076.2
Auxiliary (Front) Standard		3/4	19	18x19 rotation resistant – right regular lay (Type RB)	12,920	5 860.5
Winch	Optional	3/4	19	36x7 rotation resistant – right regular lay (Type ZB)	15,600	7 076.2

- 2M Main and Optional Auxiliary Winches

 Bi-directional gear-type (2-speed) hydraulic motors driven through planetary reduction unit for positive control under all load conditions.
- Grooved lagging
- Power up/down mode of operation
- · Hoist drum cable follower
- Drum rotation indicator
- Drum diameter: 16 in (40.6cm)
- Rope length:
 - Main: 600 ft (182.9m)
 - Auxiliary: 600 ft (182.9m)
- Maximum rope storage: 834 ft (254.2m)
- · Terminator style socket and wedge

Third wrap indicator - optional - Visually and audibly warns the operator when the wire rope is on the first/bottom layer and when the wire rope is down to the last three wraps.

Hydraulic System

Counterbalance Valves - All hoist motors, boom extend cylinders, and boom hoist cylinders are equipped with counterbalance valves to provide load lowering and prevents accidental load drop when hydraulic power is suddenly reduced.

Counterweight

Total of 12,500 lb (5 670kg) of counterweight bolted to the upper structure frame with capacities for the 12,500 lb (5 670kg) configuration.

3

Carrier

General

• 10 ft 10.5 in (*3.31m*) wide

• 12 ft 7 in (3.83m) wheelbase (centerline of first axle to centerline of second axle).

Frame – Box–type, torsion resistant, welded construction made of high tensile steel. Equipped with front and rear towing and tie–down lugs, tow connections, and access ladders.

Outriggers

Boxes – Two double box, front and rear welded to carrier frame.

Beams and Jacks – Four single stage beams with Confined Area Lifting Capacities (CALC^m) provide selectable outrigger extensions of full, intermediate, and retracted. Hydraulically controlled from the operator's cab with integral check valves.

Pontoons – Four lightweight, quick release, 19.25×19.25 in (48.90 x 48.90cm), steel pontoons with contact area of 307 in² (1 980.6cm²) can be stored for road travel in storage racks on the carrier.

Main Jack Reaction – 63,500 lb (*28 803kg*) force and 213 psi (*1 469kPa*) ground bearing pressure.

Steering and Axles

Steering – Four independent modes consisting of two wheel front, two wheel rear, four wheel, and crab. Each mode is controlled from the steering wheel and is selected by a switch in the operator's cab.

Drive – Two modes: 4×2 and 4×4 for off highway travel **Axle 1** – Steered, non-driven for 4×2 and steered, driven for 4×4

Axle 2 - Steered, driven

Suspension

Front - Rigid mount to the carrier frame

Rear – The rear axle is suspended on the oscillation cylinders with motion of the axle controlled by a four bar linkage system. The oscillation cylinders lockout when the upper structure rotates 2.5° past centerline.

• Hydro-gas rear suspension - optional

Tires and Wheels

Front and Rear – Four (single) 23.5 x 25–20 ply rating, earthmover type tires on steel disc wheels

Spare tires and wheels – optional

Brakes

 $\ensuremath{\textbf{Service}}$ – Full hydraulic, dual circuit, disc type brakes on all wheel ends

Parking/Emergency – Spring loaded type, acting on front axle

Electrical

Three batteries provide 12 volt operation and starting Lights

- Front lighting includes two main headlights, and two parking/directional indicators.
- Side lighting includes two parking/directional indicators per side.
- Rear lighting includes two parking/directional indicators, two parking/brake lights, and two reversing lights.
- Other equipment includes hazard/warning system, cab light, instrument panel light, and signal horn.

Engine

Specification	Cummins 6BT 5.9L
Numbers of Cylinders	6
Cycle	4
Bore and Stroke: inch (mm)	4.02 x 4.72 (102 x 120)
Piston Displacement: in ³ (<i>L</i>)	359 (<i>5.9</i>)
Max. Brake Horsepower: hp (<i>kW</i>)	165 (<i>123</i>) @ 2,500 rpm
Peak Torque: ft lb (<i>Nm</i>)	440 (597) @ 1,600 rpm
Alternator: volts – amps	12 – 130
Crankcase Capacity: qt (L)	17.2 (<i>16.3</i>)
Machanically driven for and th	

Mechanically driven fan and thermostatically controlled radiator Water/Fuel separator

- 110-volt block heater
- Ether injection package

Transmission

Powershift – Fully automatic transmission with eight speeds forward and four reverse. Rear axle disconnect for two or four wheel drive. Rear axle disconnects automatically in forward fifth and higher gears.

Carrier Speeds and Gradeability

	Funk		Spe	ed	Gradeability (@ 70% Convertor efficiency)
G	iear	Ratio	mph	km/h	% Grade
8th		0.74	25. 9	41.7	3.2
7th	Forward	1.03	18.5	29.8	5.3
6th	2WD	1.45	13.2	21.2	8.3
5th		2.03	9.4	15.1	12.5
4th		2.90	6.6	10.6	19.0
3rd	Forward	4.05	4.7	7.6	27.8
2nd	4WD	5.72	3.3	5.4	42.0
1st		7.99	2.4	3.9	65.6
4th		1.03	18.5	29.8	5.3
3rd	Reverse 2WD or	2.03	9.4	15.1	12.5
2nd	4WD	4.05	4.7	7.6	27.8
1st		7.99	2.4	3.8	65.6
Based o Crane o	n a gross vel perating ang	hicle weigh le must not	t of 80,000 exceed 3	0 lb (36 28 5° (77% g	37kg). grade).

Fuel Tank

One 75 gallon (283.9L) capacity tank

Hydraulic System

All functions are hydraulically powered allowing positive precise, control with independent or simultaneous operation of all functions.

Main Pumps

- Three fixed displacement gear pumps for the main and auxiliary winches, swing, boom hoist, and telescope circuits with a manual disconnect to aid during cold weather starts.
- One gear pump for the outriggers, power steering, brakes, and telescope circuits.
- One pressure compensated piston pump is used in the control, service brake, and counterweight removal circuits.
- Combined pump capacity of 139 gpm (526.2Lpm).

Hydraulic Reservoir – 131 gal (*495.9L*) capacity equipped with sight level gauge. Diffusers built in for deaeration.

Filtration – One 10 micron, full flow, line filter in the control circuit. All oil is filtered prior to return to sump tank. Accessible for easy filter replacement.

Pump Drive

All pumps are mechanically driven by the diesel engine. Main and auxiliary winches, swing, boom hoist, and telescope pumps are mounted to a mechanical pump disconnect on the transmission torque convertor to aid in cold weather starting.

Axle Loads

	Gross	/ehicle		Upper Fac	cing Front			Upper Fa	cing Rear	
Been evene with full tenk of fuel	Weig	ht (¹)	Front	Axles	Rear	Axles	Front	Axles	Rear	Axles
Base crane with full tank of fuel	lb	kg	lb	kg	lb	kg	lb	kg	lb	kg
	72,495	32 883	33,996	15 420	38,499	17 463	32,896	14 921	39,599	17 962
23.5R25 tires and wheels	368	167	183	83	185	84	183	83	185	84
Pintle hook, front	13	6	18	8	-5	-2	18	8	-5	-2
Pintle hook, rear	13	6	-5	-2	18	8	-5	-2	18	8
Rear steer indicator	3	1	0	0	3	1	0	0	3	1
Hydro-gas suspension	52	24	18	8	34	15	18	8	34	15
Winch roller - rear winch	93	42	-39	-18	132	60	129	59	-36	-17
Winch roller - front winch	93	42	-19	-9	112	51	109	49	-16	-7
2M auxiliary winch	19	9	-2	-0.9	21	10	21	10	-2	-0.9
600 ft (182.9m) of 3/4 in (19mm) wire rope on auxiliary winch	669	303	-88	-40	757	343	734	333	-65	-30
Air conditioning in operator's cab	315	143	74	34	241	109	231	105	84	38
360° swing lock	76	34	28	13	48	22	45	20	31	14
Emergency steer system	136	62	15	7	121	55	116	53	20	9
Fly storage brackets to boom base section for fly options	99	45	146	66	-47	-21	-51	-23	150	68
28.5 ft (8.68m) offset fly - stowed	1,291	585	2,237	1 015	-947	-430	-990	-449	2,281	1 035
28.5–51 ft (<i>8.68–15.54m</i>) offset fly – stowed	1,861	844	3,060	1 388	-1,199	544	-1,263	-573	3,124	1 417
Floodlight to boom base section	10	5	23	10	-13	-6	-13	-6	23	10
60 ton (<i>54.4mt</i>) hook block at front/rear bumper	1,109	503	1,530	694	-421	- 191	-459	-208	1,568	711
40 ton (<i>36.3mt</i>) hook ball at front/rear bumper	720	327	994	451	-274	-124	-298	- 135	1,108	462
8.5 ton (7.7 <i>mt</i>) hook ball at front/rear bumper	360	163	497	225	-137	-62	-149	-68	509	231
Auxiliary lifting sheave	91	41	257	117	-166	-75	-169	-77	260	118

Tire	Maximum Load @ 25 mph (40.2km/h)
23.5 x 25 (20–PR)	38,000 lb (<i>17 600kg</i>)
23.5R25 2 Star	37,500 lb (<i>17 010kg</i>)

(1) Adjust gross vehicle weight and axle loading according to component weight. Note: All weights are $\pm 3\%.$

General Dimensions



Not To Scale

Working Range Diagram

Working Range Diagram



○ Denotes Main Boom + 51' (15.5m) Fly – Boom Mode "B"
 ○ Denotes Main Boom + 28.5' (8.7m) Fly – Boom Mode "B"

Boom Extend Modes



Main Boom Lift Capacity Charts – Standard

	Fully Extended Outriggers 360° Rotation (All Capacities Are Listed In Pounds)											
Radius	Boom Length (ft)											
(ft)	35.5	40	50	60/60.3	70	80	90	100	110	(ft)		
10	100,000	78,400	72,600							10		
12	73,900	73,100	65,600	50,900**	37,900					12		
15	63,200	63,000	57,500	46,900**	37,900	35,400				15		
20	50,300	50,100	47,600	39,200**	37,900	34,700	28,900			20		
25	39,000	38,900	38,500	37,900	37,900	34,200	28,200	24,000	19,500	25		
30		31,300	31,900	32,300	32,500	30,300	24,800	22,500	19,500	30		
35			26,100	26,500	26,700	26,900	22,000	19,900	18,300	35		
40			20,800	21,200	21,400	21,500	19,700	17,800	16,400	40		
45				17,100	17,300	17,400	17,500	15,900	14,600	45		
50				13,900	14,200	14,300	14,400	14,400	13,200	50		
55					11,900	12,100	12,200	12,200	12,100	55		
60					10,000	10,200	10,300	10,300	10,400	60		
65						8,600	8,700	8,800	8,900	65		
70						7,300	7,500	7,500	7,600	70		
75							6,400	6,500	6,500	75		
80							5,400	5,500	5,600	80		
85								4,700	4,800	85		
90								4,000	4,100	90		
95									3,500	95		
100									2,900	100		
* Special (** 60.3 A-	Conditions C max Mode	Dr Wire Rope	e Required									

This information is not for crane operation. Operator must refer to the in-cab information for crane operation. Rated lifting capacities shown on fully extended outriggers do not exceed 85% of the tipping loads and on tires do not exceed 75% of the tipping loads.

On Tires – Stationary – Boom Centered Over Front Between Tire Tracks (All Capacities Are Listed In Pounds)										
Radius		Radius								
(ft)	35.5 40 50 60 70									
10	47,300	47,100				10				
12	41,600	41,400				12				
15	35,100	35,000	35,800			15				
20	27,400	27,300	28,200	28,500		20				
25	21,900	21,700	22,900	23,200	23,400	25				
30		16,100	16,700	17,100	17,200	30				
35			12,600	12,900	13,100	35				
40			9,700	10,100	10,300	40				
45				7,900	8,200	45				
50				6,300	6,500	50				
55					5,200	55				
60					4,200	60				

On Tires – Pick & Carry (Creep) – Boom Centered Over Front (All Capacities Are Listed In Pounds)

Radius		Radius				
(ft)	35.5	40	50	60	70	(ft)
10	44,100	43,900				10
12	38,400	38,200				12
15	31,800	32,000	32,400			15
20	24,000	24,300	24,700	25,000		20
25	18,600	19,000	19,500	19,800	19,900	25
30		15,100	15,600	15,900	16,100	30
35			12,600	12,900	13,100	35
40			9,700	10,100	10,300	40
45				7,900	8,200	45
50				6,300	6,500	50
55					5,200	55
60					4,200	60

On Tires – Stationary – 360° Rotation (All Capacities Are Listed In Pounds)											
Radius		Radius									
(ft)	35.5	40	50	60	70	(ft)					
10	37,200	37,400	37,700			10					
12	31,100	31,400	31,800			12					
15	24,000	24,400	24,900			15					
20	14,500	14,800	15,400	15,700		20					
25	9,400	9,800	10,300	10,700	10,900	25					
30		6,600	7,100	7,500	7,700	30					
35			5,000	5,300	5,500	35					
40			3,400	3,700	3,900	40					
45				2,500	2,700	45					

This information is not for crane operation. Operator must refer to the in-cab information for crane operation. Rated lifting capacities shown on fully extended outriggers do not exceed 85% of the tipping loads and on tires do not exceed 75% of the tipping loads.

Fully Extended Outriggers - 360° Rotation (All Capacities Are Listed In Pounds) 110 ft Main Boom Length 110 ft Main Boom Length 110 ft Main Boom Length 2° Fly Offset 40° Fly Offset 20° Fly Offset Fly Length (ft) Fly Length (ft) Fly Length (ft) Radius Radius Radius (ft) (ft) (ft) 28.5 28.5 28.5 51 51 51 35 9,400 45 9,500 50 7,500 40 9,400 50 9.100 55 7,300 45 9,400 6,200 55 8,400 60 7,100 50 9,400 6,200 60 7,800 4,800 65 6,900 55 9,200 6,200 65 7,300 4,600 70 6,500 60 8.500 6,200 70 6,800 4.400 75 6,100 3,400 65 7.900 6.000 75 6.400 4,300 80 5,800 3.400 70 7,300 5,700 80 6,000 4,100 85 5,500 3,300 85 75 6,800 5,300 5,700 4,000 90 5,200 3,200 6,200 4,900 90 5,000 3,800 95 4,600 3,200 80 85 5,300 4,600 95 4,300 3,700 100 3,900 3,100 90 4,600 4,300 100 3,700 3,500 105 3,300 3,100 4,000 105 2,800 3,000 95 4,000 3,200 3,300 110 3,500 3,800 110 2,700 3,200 2,900 100 115 3,000 3,500 115 2,300 120 2,800 105 3,000 2,500 2,400 110 3,000 120 2,600 125

2,200

1,900

130

Fly Attachment Lift Capacity Charts – Optional

This information is not for crane operation. Operator must refer to the in-cab information for crane operation. Rated lifting capacities shown on fully extended outriggers do not exceed 85% of the tipping loads and on tires do not exceed 75% of the tipping loads.

115

120

2,100

2,600

2,200

125

130

2,000

Main Boom Lift Capacity Charts – Optional (Metric)

Fully Extended Outriggers 360° Rotation (All Capacities Are Listed In Kilograms)										
Radius				Boo	m Length (m)				Radius
(m)	10.82	12.2	15.2	18.3/18.38	21.3	24.4	27.4	30.5	33.53	(m)
3.0	45 350	35 550	33 250							3.0
3.5	34 550	34 050	30 550							3.5
4.0	31 550	31 350	28 350	23 050**	17 150					4.0
4.5	29 000	28 900	26 350	21 450**	17 150					4.5
5.0	26 750	26 700	24 650	20 200**	17 150	16 050				5.0
6.0	23 100	23 050	21 850	17 950**	17 150	15 700	13 100			6.0
7.0	19 650	19 600	19 450	17 150	17 150	15 700	13 100	10 850		7.0
8.0	16 650	16 850	17 100	17 150	16 600	15 050	12 400	10 850	8 800	8.0
9.0	13 000	14 400	14 700	14 800	14 900	13 850	11 400	10 300	8 800	9.0
10.0		11 700	12 050	12 150	12 200	12 250	10 500	9 500	8 750	10.0
12.0			8 550	8 700	8 800	8 850	8 900	8 200	7 550	12.0
14.0				6 550	6 650	6 700	6 750	6 750	6 500	14.0
16.0				5 050	5 200	5 250	5 300	5 350	5 350	16.0
18.0					4 100	4 200	4 250	4 250	4 300	18.0
20.0						3 350	3 400	3 450	3 450	20.0
22.0						2 700	2 750	2 800	2 850	22.0
24.0							2 250	2 300	2 350	24.0
26.0								1 850	1 900	26.0
28.0								1 500	1 550	28.0
30.0									1 250	30.0
* Special (** 18.38 A	Conditions C	or Wire Rope	e Required							

This information is not for crane operation. Operator must refer to the in-cab information for crane operation. Rated lifting capacities shown on fully extended outriggers do not exceed 75% of the tipping loads and on tires do not exceed 65% of the tipping loads.

On Tires – Stationary – Boom Centered Over Front Between Tire Tracks (All Capacities Are Listed In Kilograms)								
Radius			Boom Length (m)			Radius		
(m)	10.82	12.2	15.2	18.3	21.3	(m)		
3	21 700					3		
3.5	19 500	19 400				3.5		
4	17 650	17 600				4		
4.5	16 150	16 250	16 450			4.5		
5	14 800	14 950	15 150			5		
6	12 650	12 750	12 950	13 100		6		
7	10 150	10 300	10 550	10 650	9 900	7		
8	7 900	8 100	8 350	8 450	8 500	8		
9	6 300	6 500	6 750	6 900	6 950	9		
10		5 350	5 600	5 750	5 800	10		
12			3 950	4 100	4 200	12		
14				3 000	3 050	14		
16				2 200	2 300	16		
18					1 700	18		

On Tires – Pick & Carry (Creep) – Boom Centered Over Front (All Capacities Are Listed In Kilograms)							
Radius			Boom Length (m)			Radius	
(m)	10.82	12.2	15.2	18.3	21.3	(m)	
3	20 250	Ì				3	
3.5	18 000	17 950				3.5	
4	16 200	16 300				4	
4.5	14 600	14 750	14 900			4.5	
5	13 250	13 400	13 550			5	
6	11 050	11 200	11 400	11 500		6	
7	9 350	9 500	9 700	9 850	9 900	7	
8	7 900	8 100	8 350	8 450	8 500	8	
9	6 300	6 500	6 750	6 900	6 950	9	
10		5 350	5 600	5 750	5 800	10	
12			3 950	4 100	4 200	12	
14				3 000	3 050	14	
16				2 200	2 300	16	
18					1 700	18	

This information is not for crane operation. Operator must refer to the in-cab information for crane operation. Rated lifting capacities shown on fully extended outriggers do not exceed 75% of the tipping loads and on tires do not exceed 65% of the tipping loads.

On Tires – Stationary – 360° Rotation (All Capacities Are Listed In Kilograms)							
Radius			Boom Length (m)			Radius	
(m)	10.82	12.2	15.2	18.3	21.3	(m)	
3	17 100					3	
3.5	14 750	14 900				3.5	
4	11 850	12 000				4	
4.5	9 700	9 850	10 050			4.5	
5	8 100	8 250	8 450			5	
6	5 850	6 000	6 200	6 350		6	
7	4 400	4 550	4 750	4 900	4 950	7	
8	3 300	3 450	3 700	3 800	3 900	8	
9	2 500	2 650	2 900	3 050	3 1 0 0	9	
10		2 050	2 300	2 400	2 500	10	
12			1 400	1 500	1 600	12	
14					1 000	14	

Fly Attachment Lift Capacity Charts – Optional (Metric)

	Fully Extended Outriggers – 360° Rotation (All Capacities Are Listed In Kilograms)							
33.53n	n Main Boom I 2 [°] Fly Offset	Length	33.53r	n Main Boom 20° Fly Offset	Length	33.53r	n Main Boom 40° Fly Offset	Length
Radius	Fly Len	gth (m)	Radius	Fly Len	gth (m)	Radius	Fly Len	gth (m)
(m)	8.69	15.54	(m)	8.69	15.54	(m)	8.69	15.54
12	4 250		14	4 250		16	3 350	
14	4 250	2 800	16	4 000		18	3 250	
16	4 250	2 800	18	3 600	2 200	20	3 100	
18	3 900	2 800	20	3 300	2100	22	2 850	1 600
20	3 550	2 700	22	3 000	1 950	24	2 650	1 550
22	3 050	2 500	24	2 750	1 850	26	2 400	1 500
24	2 550	2 250	26	2 300	1 800	28	2 000	1 450
26	2 100	2 050	28	1 900	1 700	30	1 650	1 400
28	1 750	1 900	30	1 550	1 650	32	1 350	1 400
30	1 450	1 650	32	1 250	1 500	34	1 050	1 350
32	1 150	1 350	34	1 000	1 300	36		1 200
34	950	1 1 50	36	800	1 100	38		950
36		950	38		900	40		750

This information is not for crane operation. Operator must refer to the in-cab information for crane operation. Rated lifting capacities shown on fully extended outriggers do not exceed 75% of the tipping loads and on tires do not exceed 65% of the tipping loads.

5472 (supersedes 5427)-0506-J6

Link-Belt Construction Equipment Company Lexington, Kentucky www.linkbelt.com ®Link-Belt is a registered trademark. Copyright 2006. We are constantly improving our products and therefore reserve the right to change designs and specifications.



Specifications

Telescopic Boom Rough Terrain Crane

RTC-8050 50-ton (45.36 metric ton) **Series** *II*





General	Dimensions	feet	metric		
Turning Radius	(4-wheel steer -centerline				
of tires	,	20'	6.09		
Turning Radius	(2-wheel steer -centerline				
of tires		36'	10.97		
Turning Radius	(4-wheel steer - outside				
front carrier cor	mer	23' 4"	7.11		
Turning Radius	(2-wheel steer - outside				
front carrier cor	ner	39' 0"	11.89		
Tailswing of cou	unterweight	12' 10"	3.90		
	Tire	Size			
Dimension	23.5 x 25	23.5 R 25			
Α	10' 3.5" <i>(3.14 m)</i>	10' 3" <i>(3.1</i>	10' 3" <i>(3.12 m)</i>		
В	6' 7.75" <i>(2.03 m)</i>	6' 9.5" <i>(2.06 m)</i>			
С	11' 11.75" <i>(</i> 3.65 <i>m</i>)	12' 1.5" <i>(</i> 3.70 m)			
D	7.75" <i>(0.20 m)</i>	7" (0.18 m)			
E	10" <i>(0.25 m)</i>	11.75" <i>(0.30 m)</i>			
F	10' 0.25" <i>(3.05 m)</i>	10' 2" <i>(</i> 3.1	0 m))		
G	7' 6" <i>(</i> 2.29 <i>m</i>)	7' 7.75" (2.33 m			
н	24°	24.8°			
J	21°	22°			
к	6' 6.75" <i>(1.69 m)</i>	6' 8.5" (1.7	74 m)		
L	8' 3" <i>(</i> 2.51 <i>m</i>)	8' 3" <i>(</i> 2.51	<i>m)</i>		

Litho in U.S.A. 8/01

#5334 (Supersedes #5326)



Upper Structure

Boom

Patented Design

- Boom side plates have diamond shaped impressions for superior strength to weight ratio and 100,000 p.s.i. (689.5 MPa) steel angle chords for lateral stiffness.
- Boom telescope sections are supported by top, bottom and adjustable side wear shoes to prevent metal to metal contact.

Standard Boom

- 35.5' 110' (10.82 33.53 m) four-section full power boom.
 - · Basic mode (or mode 'B') is the full power, synchronized mode of telescoping all sections proportionally.
- The exclusive A-max mode (or mode 'A') extends only the inner mid-section to 60.3' (18.38 m) offering increased capacities for in-close, maximum capacity picks.
- Mechanical Boom Angle Indicator

Boom Head

- Four 16.5" (0.42 m) root diameter nylon sheaves handle up to eight parts of wire rope
- Quick-reeve design
- Rope dead end lugs provided on each side of boom head
- Easily removable wire rope guards
- Fly pinning alignment tool

Boom Elevation

- One Link-Belt designed hydraulic cylinder with holding valve and bushing in each end.
- Hand control for controlling boom elevation from -3° to 78°

Optional Auxiliary Lifting Sheave

- Single 16.5" (0.42 m) root diameter nylon sheave with removable wire rope guard.
- Use with one or two parts of line.
- Does not affect erection of fly or use of main head sheaves for multiple reeving.

Optional

- 60-ton (54.43 mt) 4-sheave, quick reeve™ hook block
- 40-ton (36.29 mt) 4-sheave, quick reeve[™] hook block
- 8.5-ton (7.7 mt) hook ball (swivel or nonswivel)
- · Boom floodlight

Flv

Optional

- 28.5' (8.69 m) One-piece lattice fly, stowable, offsettable to 2°, 20° or 40°.
- Lugs to allow for second section.
- 28.5' 51' (8.69 15.54 m) Two-piece (bifold) stowable, offsettable to 2°, 20° or 40°.

Cab and Controls

Environmental ULTRA CAB

RTC-8050 Series II

LCF-2000 construction process featuring laminated fibrous composite material.

- Isolated from sound with acoustical vinyl insulation.
- Six-way adjustable operator's seat with retractable seat belt.
- Four-way adjustable tilting-telescoping . and locking steering wheel.
- All windows are tinted and tempered safety glass.
- Slide by door opens to 3' (0.91 m) width. Sliding rear and right side windows and swing up roof window for maximum visibility and ventilation.
 - Audible swing alarm · Warning horn
 - Backup alarm
 - Travel lights 12-volt accessory outlet Sun screen
 - Electric windshield wiper Mirrors
 - Top hatch window wiper Cup holder · Circulating fan
- Fire extinguisher
- Windshield washer ٠

Optional

- Amber strobe light
- Emergency steering system
- Hot water cab heater
- Amber rotating beacon
- Air conditioning

Controls

Hydraulic controls (joystick type) for: Boom hoist Rear winch

- Optional front winch
- ٠ Drum rotation indicators
- Single-axis optional
- Hand-held outrigger controls and sight level bubble also provided in upper cab.

Swing

Fuel

Actual load

· Boom angle

· Allowed load

Radius of load

Foot controls for:

- Boom telescope
- Swing brake
- Engine throttle with throttle lock

Cab Instrumentation

Corner-post mounted gauges with integral audio/visual warning system for: Voltmeter

- Tachometer
- Oil pressure
- Convertor temperature
- Hvdraulic oil temperature
- Water temperature

Rated Capacity Limiter

- Microguard 434 Graphic audio-visual warning system built into the cornerpost with anti-two block and function limiters.
- Anti-two block weight designed for quick reeve of hookblock.

Operating data available includes:

- Machine configuration
- Boom length
- Head height
 - % of allowed load

Presettable alarms include:

- Maximum and minimum boom angles.
- Maximum tip height.
- Maximum boom length.
- Swing left/right positions.

Operator defined area alarm is standard.

-2-

Optional

- Internal RCL light bar: Visually informs operator when crane is approaching maximum load capacity with a series of green, yellow and red lights.
- External RCL light bar: Visually informs ground crew when crane is approaching maximum load capacity kickouts and presettable alarms with a series of three lights; green, yellow and red.

Swing

- Bi-directional hydraulic swing motor mounted to a planetary reducer for 360° continuous smooth swing at 2.8 r.p.m.
- Swing park brake 360° electric over hydraulic (spring applied, hydraulic released) multi-disc brake mounted on the speed reducer. Operated by toggle switch in overhead control console.
- Swing brake 360°, foot operated, hydraulic applied disc brake mounted on the speed reducer.
- Swing lock Standard; two position travel lock operated from the operator's cab.
- Counterweight 12,500 lbs. (5 670 kg) Bolted to upper structure frame.

Optional

360° pawl-in-gear swing lock (meets New York City requirements).

Combined pump capacity 117 gpm (443

powered by engine through a pump dis-

Pump disconnect is a spline-type clutch

Pump operates at 3,500 p.s.i. (24.1 MPa)

O-Ring Face Seal (ORFS) technology

Telescope / Outrigger / Steering Pump -

maximum. Mounted on transmission,

powered by engine through a direct me-

Pump operates at 3,000 p.s.i. (20.7 MPa)

Single gear-type pump, 22 gpm (83 lpm)

throughout with hydraulic oil cooler.

Mounted on transmission converter,

engaged/disengaged from carrier.

maximum system pressure.

maximum system pressure.

140 gal. (303 L) capacity. Diffuser for

One 10-micron filter located inside

Accessible for easy replacement.

· Five separate, pilot operated control

Winch control valves are pressure

compensated for improved metering.

valves allow simultaneous operation of all

Hydraulic System

Main Pump

lpm)

connect.

chanical drive.

Reservoir

Filtration:

deaeration.

Control Valves:

crane functions.

hydraulic reservoir.

Three-section gear-type pump.



Load Hoist System

Standard

- 2M rear winch with grooved lagging.
- Two-speed motor and automatic brake.
- Power up/down mode of operation. •
- Controls for future addition of front winch. Bi-directional gear-type hydraulic motor, driven through a planetary reduction unit for positive operator control under all load
- · Asynchronous parallel double crossover grooved drums minimize rope harmonic motion.
- · Rotation resistant wire rope.

Line Pulls and Speeds

 Maximum line pull 15,390 lbs. (6 980 kg) and maximum line speed of 455 f.p.m. (139 m/min) on standard 16" (0.41 m) root diameter grooved drum.

Optional

- 2M front winch with two-speed motor, automatic brake, grooved lagging and power up/down mode of operation.
- Hoist drum cable followers.
- Third wrap indicators.

Carrier

conditions.

- 10' 6" (3.20 m) wide, 161" (4.09 m) wheelhase
- 4 x 4 x 4 (4–wheel steer, 4–wheel drive) For rough terrain with limited turning area.

Frame

- 100,000 p.s.i. (689.5 MPa) steel, double walled construction.
- Integral 100,000 p.s.i. (689.5 MPa) steel outrigger boxes.

Standard Carrier Equipment

- · Two front, two rear, and two mid-point carrier steps
- · Non-slip safety strips on carrier deck
- Deep front storage unit
- · Full deck fenders
- Pontoon storage
- Full lighting package •
- Front towing shackles
- Hook block tie back

Optional

Front and rear mounted pintle hook

Engine

Engine	Cummins 6BT 5.9 L
Cylinders – cycle	6 – 4
Bore	4.02 in. (102.11 mm)
Stroke	4.72 in. <i>(119.89 mm)</i>
Displacement	359 cu. in. <i>(5.9 L)</i>
Maximum brake hp	185 @ 2,500 rpm
Peak torque (ft. lb.)	553 @ 1,500 rpm
Electric system	12 volt
Starting system	12 volt
Fuel capacity	75 gallons <i>(</i> 283.9 L)
Alternator	130 amps
Crankcase capacity	17.2 qts. (16.3 L)
(total system)	
 Water/fuel separator 	on engine

- 110-volt block heater
- Ether injection package optional

Transmission

- Funk DF-150 power shift transmission with eight speeds forward and four reverse.
- Rear axle disconnect for two or fourwheel drive.
- LCD indicator providing gear and diagnostic information.

Axles

Front and Rear Axles

Heavy duty planetary drive/steer type

Suspension

Front Axle

· Rigid mounted to frame

Rear Axle

- Fully independent 4-Link
- Automatic axle oscillation lockout cylinders engage when upper structure rotates past 2.5° of centerline

Optional

Rear Hydro–gas Ride[™]

Steering

- Hydraulic front-wheel, rear-wheel, fourwheel and "crab" steering
- Modes selected by rotary switch on overhead console.
- All modes are fully coordinated and controlled by steering wheel.

Optional

· Rear steer indicator

Tires

Front and Rear

 Standard 23.5 x 25 (20–PR) Earthmover type.

Optional

- 23.5R25 2 star radials
- · Spare tires and rims

Brakes

Service

Fully hydraulic disc-type brakes at each wheel end with independent front and rear system. Controlled by foot pedal in cab.

Parking/Emergency

Spring applied, hydraulic released, cab controlled, wet, multiple disc-type integral to the transmission.

Outriggers

- Three position operation capability.
- Four hydraulic, telescoping beam and jack outriggers.
- Vertical jack cylinders equipped with integral holding valve.
- Beams extend to 22' 6" (6.86 m) centerline-to-centerline and retract to within 10' 6" (3.20 m) of the overall crane width.
- Equipped with stowable, lightweight 19" (0.48 m) square steel pontoons.
- Hand-held controls and sight level bubble located in upper structure cab.

Confined Area Lifting Capacities (CALC[™]) System

- Three operational outrigger configurations are available:
 - Full extension 22' 6" (6.86 m)
 - Intermediate position -17' 6" (4.33 m)Full retraction -9' 7" (2.92 m)
- · For confined area operation, rated lifting capacities are provided for the intermediate and fully retracted outrigger positions.
- When the outrigger position levers (located on the outrigger beams) are engaged, the operator can set the crane in the intermediate or full retraction outrigger position without leaving the cab.

Travel Speeds and Gradability

Tires	23.5 x 25 (20–PR)
Maximum Speed	25 (40.23 km/h)
Gradability at stall	90%
Maximum Tractive Effort at Stall	53,765 lbs. <i>(24 387 kg)</i>
Gradability at 1.0 mph (1.6 km/hr)	60%
Maximum Tractive Effort at 1.0 mph. (1.6 km/hr)	34,250 lbs. @ 1,500 rpm <i>(15 536 kg)</i>



Axle Loads

Base machine with standard $35.5' - 110'$	G.V.W.		Upper facing front				Upper facing rear			
main winch with 2–speed hoisting and pow- er up/down. 600' (182.88 m) of 3/4"			Front axle		Rear axle		Front axle		Rear	axle
(19 mm) wire rope. 4x4x4 carrier with Cum- mins 6BTA5.9 engine, 23.5x25 tires, 75	lbs.	kg.	lbs.	kg.	lbs.	kg.	lbs.	kg.	lbs.	kg.
gals. <i>(283.91 L)</i> of fuel, tow shackles and hook block tieback.	72,430	32 853	34 013	15 428	38,417	17 426	31,307	14 201	38,106	17 285
Cold weather starting aids - ether injector	6	3	-2	-0.9	8	4	-2	-0.9	8	4
23.5R25 Tires	428	194	213	97	215	98	213	97	215	98
Pintle hook, front	13	6	18	8	-5	-2	18	8	-5	-2
Pintle hook, rear	13	6	-5	-2	18	8	-5	-2	18	8
Rear steer indicator	3	1	0	0	3	1	0	0	3	1
Hydro–gas Suspension	52	24	18	8	34	15	18	8	34	15
Winch roller – rear winch	93	42	-39	-18	132	60	129	59	-36	-17
Winch roller – front winch	93	42	-19	-9	112	51	109	49	-16	-7
2M Auxiliary Winch	19	9	-2	-0.9	21	10	21	10	-2	-0.9
600' <i>(182.88 m)</i> of 3/4" <i>(19 mm)</i> wire rope on auxiliary winch	669	303	-88	-40	757	343	734	333	-65	-30
Cab heater	50	23	25	11	25	11	23	10	27	12
Air conditioning in operator's cab	315	143	74	34	241	109	231	105	84	38
360 degree swing lock	76	34	28	13	48	22	45	20	31	14
Emergency steer system	136	62	15	7	121	55	116	53	20	9
Fly brackets to boom base sections for fly options	99	45	146	66	-47	-21	-51	-23	150	68
28.5' (8.68 m) fixed fly (stowed)	1,291	585	2,237	1 015	-947	-430	-990	-449	2,281	1 035
28.5' – 51' <i>(8.68 – 15.54 m)</i> offset fly (stowed)	1,861	844	3,060	1 388	-1,199	-544	-1,263	-573	3,124	1,417
Floodlight to boom base section	10	5	23	10	-13	-6	-13	-6	23	10
60–ton <i>(54.43 mt)</i> capacity hook block to front/rear bumper	1,109	503	1,530	694	-421	-191	-459	-208	1 568	711
40-ton (36.29 mt) capacity hook block to front/rear bumper	720	327	994	451	-274	-124	-298	-135	1,108	462
8.5–ton (7.7 <i>mt</i>) capacity hook block to front/rear bumper	360	163	497	225	-137	-62	-149	-68	509	231
Auxiliary lifting sheave	91	41	257	117	-166	-75	-169	-77	260	118

 \square – Adjust gross weight and axle loading according to component weight. Note: All weights are \pm 3%.

Tire	Max. Axle Load @ 25 mph (40.23 km/hr)
23.5 x 25 (20–PR)	38,800 (17 600 kg)
23.5R25 2 Star	38,800 <i>(17 600 kg)</i>

Link-Belt Construction Equipment Company Lexington, Kentucky www.linkbelt.com [®]Link-Belt is a registered trademark. Copyright 2001. All rights reserved. We are constantly improving our products and therefore reserve the right to change designs and specifications. RTC-8050 Series II



Lifting Capacities

Telescopic Boom Rough Terrain Crane

RTC-8050 Series II

50-ton (45.36 metric tons)

Boom and Fly Capacities for this machine are listed by the following sections.

Fully Extended Outriggers

- Working Range Diagram
- 35.5' to 60.3' (10.82 18.38 m) Main Boom Capacities, "A-max" Mode
- 35.5' to 110' (10.82 33.53 m) Main Boom Capacities, Basic Mode "B"
- 28.5' (8.69 m) One-piece Fly Capacities, Basic Mode "B"
- 28.5' to 51' (8.69 15.54 m) Two-piece Fly Capacities, Basic Mode "B"

On Tires

- Working Range Diagram
- 35.5' to 60.3' (10.82 18.38 m) Main Boom Capacities, "A-max" Mode
- 35.5' to 70' (10.82 21.34 m) Main Boom Capacities, Basic Mode "B"



CAUTION: This material is supplied for reference use only. Operator must refer to in-cab Crane Rating Manual to determine allowable machine lifting capacities and operating procedures.



READ AND UNDERSTAND THE OPERATOR'S AND SAFETY MANUALS AND THE FOLLOWING INSTRUCTIONS AND RATED LIFTING CAPACITIES BEFORE OPERATING CRANE. OPERATION WHICH DOES NOT FOLLOW THESE INSTRUCTIONS MAY RESULT IN AN ACCIDENT

OPERATING INSTRUCTIONS GENERAL:

- 1. Rated lifting capacities in pounds as shown on lift charts pertain to this crane as originally manufactured and normally equipped. Modifications to the crane or use of optional equipment other than that specified can result in a reduction of capacity.
- 2. Construction equipment can be dangerous if improperly operated or maintained. Operation and maintenance of this crane must be in compliance with the information in the Operator's, Parts, and Safety Manuals supplied with this crane. If these manuals are missing, order replacements through the distributor.
- 3. The operator and other personnel associated with this crane shall read and fully understand the latest applicable American National Standards ASME B30.5 safety standards for cranes.
- 4. The rated lifting capacities are based on crane standing level on firm supporting surface.

SET UP:

- 1. The crane shall be leveled on a firm supporting surface. Depending on the nature of the supporting surface, it may be necessary to have structural supports under the outrigger pontoons or tires to spread the load to a larger bearing surface.
- 2. When making lifts on outriggers, all tires must be free of supporting surface. All outrigger beams must be extended to the same length; fully retracted, intermediate extended, or fully extended.
- When operating on tires over the side, do not exceed 71° maximum boom angle. Loss of backward stability will occur causing a backward tipping condition.
- 4. When making lifts on tires, they must be inflated to the recommended pressure. (See Operation note 20 and Tire Inflation.)
- 5. For required parts of line, see Wire Rope Capacity and Winch Performance.
- 6. Before setting up on intermediate outriggers, retracted outriggers, or tires, refer to Working Range Diagrams and rated lifting capacities to determine allowable crane configurations.

OPERATION:

- Rated lifting capacities at rated radii shall not be 1. exceeded. Do not tip the crane to determine allowable loads. For concrete bucket operation, weight of bucket and load shall not exceed 80% of rated lifting capacities. For clamshell bucket operation, weight of bucket and bucket contents is restricted to a maximum weight of 6000 pounds or 80% of rated lifting capacity, whichever is less. For magnet operation, weight of magnet and load is restricted to a maximum weight of 6000 pounds or 80% of rated lifting capacity, whichever is less. For clamshell and magnet operation, maximum boom length is restricted to 50 feet and the boom angle is restricted to a minimum of 35 degrees. Lifts with any fly erected are prohibited for both clam and magnet operation.
- 2. Rated lifting capacities shown on fully extended outriggers do not exceed 85% of the tipping loads. Rated lifting capacities shown on intermediate extended or fully retracted outriggers are determined by the formula, rated load = (tipping load $0.1 \times 1000 \text{ factor} / 1.25$. Rated lifting capacities shown on tires do not exceed 75% of the tipping loads. Tipping loads are determined by SAE crane stability test code J–765.
- Rated lifting capacities in the shaded areas are based on structural strength or hydraulic limitations and have been tested to meet minimum requirements of SAE J–1063 cantilevered boom crane structures–method of test. Rated lifting capacities in the non–shaded areas are based on stability ratings. Some capacities are limited by a maximum obtainable 78° boom angle.
- 4. Rated lifting capacities include the weight of hook ball/block, slings, bucket, magnet and auxiliary lifting devices. Their weights must be subtracted from the listed rated capacity to obtain the net load that can be lifted. Rated lifting capacities include the deduct for either fly stowed on the base of the boom. For deducts of either fly erected, but not used, see Capacity Deductions For Auxiliary Load Handling Equipment.
- 5. Rated lifting capacities are based on freely suspended loads. No attempt shall be made to move a load horizontally on the ground in any direction.
- 6. Rated lifting capacities are for lift crane service only.
- 7. Do not operate at radii or boom lengths (minimum or maximum) where capacities are not listed. At these positions, the crane can tip or cause boom failure.



- 8. definable because of variation in loadings and crane maintenance, but it is permissible to attempt retraction and extension within the limits of the applicable load rating chart.
- 9. For main boom capacities when either boom length or radius or both are between values listed, proceed as follows:

a. For boom lengths not listed, use rating for next longer boom length or next shorter boom length, whichever is smaller.

b. For load radii not listed, use rating for next larger radius.

- 10. The user shall operate at reduced ratings to allow for adverse job conditions, such as: soft or uneven ground, out of level conditions, wind, side loads, pendulum action, jerking or sudden stopping of loads, hazardous conditions, experience of personnel, traveling with loads, electrical wires, etc. Side load on boom or fly is dangerous and shall be avoided.
- 11. Shock loading the boom shall be avoided. However, in cold weather, if it is believed that shock loads may occur, rated capacities should be reduced by the following rule: a 1% reduction in rated capacities should be taken for each 1°F below 0°F.
- 12. When making lifts with auxiliary head machinery, the effective length of the boom increases by 2 feet.
- 13. Power sections of boom must be extended in accordance with boom mode "A" or "B". In boom mode "B" all power sections must be extended or retracted equally.
- 14. The least stable rated working area depends on the configuration of the crane set up.
- 15. Rated lifting capacities are based on correct reeving. Deduction must be made for excessive reeving. Any reeving over minimum required (see Wire Rope Capacity) is considered excessive and must be accounted for when making lifts. Use Working Range Diagram to estimate the extra feet of rope then deduct 1 lb. for each extra foot of wire rope before attempting to lift a load.
- 16. The loaded boom angle combined with the boom length give only an approximation of the operating radius. The boom angle, before loading, should be greater to account for deflection. For main boom capacities, the loaded boom angle is for reference only. For fly capacities, the load radius is for reference only.
- 17. For fly capacities with main boom length less than 110 ft. and greater than 90 ft., the rated loads are determined by the boom angle using the 110 ft. boom and fly chart. For angles not shown use the next lower boom angle to determine the rated capacity.

- The maximum loads that can be telescoped are not 18. For fly capacities with main boom length less than 90 ft. the rated loads are determined by the boom angle only using the 90 ft. boom and fly chart. For angles not shown, use the next lower boom angle to determine the rated capacity.
 - 19. The 35.5 ft. boom length structural capacities are based on boom fully retracted. If the boom is not fully retracted, do not exceed capacities shown for the 40 ft. boom length.
 - 20. Rated lifting capacities on tires depend on tire capacity, condition of tires, and tire air pressure. On tire capacities require lifting from main boom head only on a smooth and level surface. Pick and carry operations are restricted to speed of 2.5 mph and creep . The boom must be centered over the front of the crane with two-position travel swing lock engaged and the load must be restrained from swinging. Lifts with any fly erected on tires are prohibited. For correct tire pressure, see Tire Inflation.

DEFINITIONS:

- 1. Load Radius: Horizontal distance from a projection of the axis of rotation to the supporting surface, before loading, to the center of the vertical hoist line or tackle with load applied.
- 2. Loaded Boom Angle: \measuredangle The angle between the boom base section and horizontal with freely suspended load at the rated radius.
- 3. Working Area: Area measured in a circular arc about the center line of rotation as shown on the Working Area Diagram.
- Freely Suspended Load: Load hanging free with no 4. direct external force applied except by the hoist line.
- 5. Side Load: Horizontal side force applied to the lifted load either on the ground or in the air.
- No Load Stability Limit: The radius or boom angle 6. beyond which it is not permitted to position the boom because the crane can overturn without any load on the hook.
- Load Factor: Load applied at the boom tip which gives 7. the same moment effect as the boom mass.
- Creep: Crane movement limited to 200 ft. in a 30 minute 8. period and not to exceed 1 mph maximum speed.



TIRE INFLATION

Tire Size	Operation	Tire Pressure (psi)
00 F X 05	Stationary	85
20.5 X 25 24 Ply Rating	Creep	85
24 Fly Rauliy	2.5 m.p.h.	85
00 5005	Stationary	102
20.5K25 2 Star Rating	Creep	102
2 Giai Maling	2.5 m.p.h.	102

PONTOON LOADINGS

Maximum Pontoon Load	Maximum Pontoon Ground Bearing Pressure:
63,500 lb	213 psi

BOOM MODES



WIND SPEED RESTRICTIONS

If The Wind Speed Exceeds:	Rated Lifted Capacities Must Be Reduced By At Least:			
20 MPH	40%			
30 MPH	70%			
40 MPH	Crane operation must be shutdown and the boom retracted and lowered to horizontal.			
 Additional reductions are required for loads with large wind sail area. 				

- These restrictions are based on machine on fully extended outriggers.
- The operator shall add 10° to all minimum boom angles due to no load stability and shall not boom down below that angle.

WINCH PERFORMANCE

	Winch Line Pu	Drum Rope Capacity				
	Two Spee	(F	t.)			
Wire	Low Speed	High Speed				
Rope Layer	Available Lbs.*	Available Lbs.	Layer	Total		
1	15,390	7,302	114	114		
2	14,150	6,714	124	238		
3	13,094	6,213	134	372		
4	12,185	5,781	144	516		
5	11,394	5,406	154	670		
* Maximum lifting capacity: Type RB Rope = 12,920 Type ZB Rope = 15,600						

WIRE ROPE CAPACITY

Maximum Lifting Capacities Based On Wire Rope Strength							
Parts of	3/4"	3/4"					
Line	Type RB	Type ZB	Notes				
1	12,920	15,600	Capacities shown are in				
2	25,840	31,200	pounds and working loads must not exceed the rat-				
3	38,760	46,800	ings on the capacity charts				
4	51,680	62,400	Manual.				
5	64,600	78,000	Study Operator's Manual				
6	77,520	93,600	for wire rope inspection procedures and single part				
7	90,440	109,200	of line application.				
8	103,360	124,800					
LBCE	DESCRIPTION						
Type RB	18 x 19 R High Stre	18 x 19 Rotation Resistant – Compacted Strand – High Strength, Preformed, Right Regular Lay					
Type ZB	36 x 7 Rc Steel – R	36 x 7 Rotation Resistant – Extra Improved Plow Steel – Right Regular Lay					

HYDRAULIC CIRCUIT PRESSURE SETTINGS

Function	Pressure (psi)
Front And Rear Winch	3,500
Outrigger	3,000
Boom Hoist	3,500
Telescope	3,000
Swing	1,500
Steering	2,500
Pilot Control	500



0

WORKING AREAS



CAPACITY DEDUCTIONS FOR AUXILIARY LOAD HANDLING EQUIPMENT

Load Handling Equipment	Weight (lbs)				
Auxiliary Head Attached	100				
40 Ton Quick Reeve 3 Sheave Hook Block (See Hook Block For Actual Weight)	720				
60 Ton Quick Reeve 3 Sheave Hook Block (See Hook Block For Actual Weight)	1109				
10 Ton Quick Reeve 3 Sheave Hook Block (See Hook Block For Actual Weight)	583				
8.5 Ton Hook Ball (See Hook Ball For Actual Weight)	360				
Lifting From Main Boom With:					
-					

28.5 or 51 Ft. Fly Stowed on Boom Base (See operation note #4) 28.5 Ft. Offset Fly Erected But Not Used 3,200

51 Ft. Offset Fly Erected But Not Used	6,800			
Lifting From 28.5 Ft. Offset Fly With:				
22.5 Ft. Fly Tip Erected But Not Used	PROHIBITED			
22.5 Ft. Fly Tip Stowed On 28.5 Ft. Offset Fly	PROHIBITED			
Note: Capacity deductions are for Link–Belt supplied equipment only.				



WORKING RANGE DIAGRAM





°<u>/0000 // 00 //00 //00</u>

Note: Refer To Page 5 For "Capacity Deductions For Auxiliary Load Handling. Equipment". \measuredangle ° Loaded Boom Angle In Degrees. () Reference Radius For Minimum Boom Angle Capacities (Shown In Parenthesis) Are In Feet.

Rated Lifting Capacities In

Pounds

Rated Liftin Pounds Fully Extend See Set Up	Rated Lifting Capacities In Pounds Fully Extended Outriggers See Set Up Note 2					
Load		35.5 Ft.			40 Ft.	
Radius (Ft.)	۲°	360°	Over Front	۲°	360°	Over Front
10	68.0	100,000	100,000	70.5	78,400	78,400
12	64.5	73,900	75,400	67.5	73,100	73,100
15	58.5	63,200	64,400	62.5	63,000	63,800
20	48.0	50,300	51,300	54.0	50,100	51,200
25	34.5	39,000	40,900	44.0	38,900	40,700
30				31.0	30,800	32,300
Min.Bm. Ang.Cap.	0 (30.0)	17,800	17,800	0 (34.5)	15,300	15,300
Load		50 Ft.	1		60.3 Ft.	i.
Radius (Ft.)	۲°	360°	Over Front	۲°	360°	Over Front
10	75.0	72,600	72,600			
12	72.5	65,600	65,600	76.5	50,900	50,900
15	69.0	57,500	57,500	73.5	46,900	46,900
20	62.5	47,600	47,600	68.5	39,200	39,200
25	55.5	38,500	40,200	63.0	33,400	33,400
30	48.0	30,500	32,100	57.5	28,700	28,700
35	39.0	24,800	26,100	51.0	24,600	25,200
40	27.5	19,100	20,400	44.0	18,900	20,200
45				36.0	14,900	16,000
50				26.0	11,800	12,800
Min.Bm. Ang.Cap.	0 (44.5)	10,100	10,100	0 (54.8)	6,500	6,500

Γ

Fully E	Set Up Note 2 FULL MAIN BOOM "B"			FULL			MAIN BOOM "B"		
Load		35.5 Et			40 Ft.			50 Ft.	
Radius (Ft.)	×°	360°	Over Front	×°	360°	Over Front	×°	360°	Over Front
10	68.0	100,000	100,000	70.5	37,900	37,900	74.5	37,900	37,900
12	64.5	73,900	75,400	67.5	37,900	37,900	72.5	37,900	37,900
15	58.5	63,200	64,400	62.5	37,900	37,900	69.0	37,900	37,900
20	48.0	50,300	51,300	54.0	37,900	37,900	62.5	37,900	37,900
25	34.5	39,000	40,900	44.0	37,900	37,900	55.5	37,900	37,900
30				31.0	31,300	32,900	48.0	31,900	33,500
35							39.0	26,100	27,500
40							27.5	20,800	22,100
Min.Bm Ang Cap	0 (30.0)	17,800	17,800	0 (34.5)	14,700	14,700	0 (44.5)	9,900	9,900
Load		60 Ft.			70 Ft.			80 Ft.	
Radius (Ft.)	ێ°	360°	Over Front	Ճ°	360°	Over Front	ێ°	360°	Over Front
10	77.5	37,900	37,900						
12	76.0	37,900	37,900	78.0*	37,900	37,900			
15	73.0	37,900	37,900	76.0	37,900	37,900	78.0*	35,400	35,400
20	68.0	37,900	37,900	72.0	37,900	37,900	74.5	34,700	34,700
25	62.5	37,900	37,900	67.5	37,900	37,900	71.0	34,200	34,200
30	56.5	32,300	33,900	62.5	32,500	32,800	67.0	30,300	30,300
35	50.5	26,500	27,800	57.5	26,700	28,100	63.0	26,900	27,200
40	43.5	21,200	22,500	52.5	21,400	22,700	58.5	21,500	22,800
45	35.5	17,100	18,200	46.5	17,300	18,400	54.0	17,400	18,500
50	25.0	13,900	14,900	40.5	14,200	15,200	49.0	14,300	15,300
55				33.0	11,900	12,700	44.0	12,100	12,800
60				23.5	10,000	10,700	38.0	10,200	10,900
65							31.0	8,600	9,300
70							22.0	7,300	7,900
MinBm Ang Cap	0 (54.5)	7,000	7,000	0 (64.5)	5,000	5,000	0 (74.5)	3,500	3,500
Load		90 Ft.			100 Ft.			110 Ft.	1
Radius (Ft.)	<u>ک</u> °	360°	Over Front	ێ°	360°	Over Front	×°	360°	Over Front
20	74.0	28,900	28,900	76.0	24.000	24.000	77 5	10 500	10 500
20	74.0	20,200	20,200	70.0	24,000	24,000	75.0	19,500	19,500
35	67.0	24,000	24,000	70.0	19 900	19 900	72.5	18 300	18 300
40	63.5	19 700	19,700	67.0	17,800	17,800	70.0	16,000	16,000
40	59.5	17,500	17,800	63.5	15,000	15,000	67.0	14 600	14 600
50	55.5	14,000	15,000	60.5	14 400	14 400	64.0	13 200	13 200
55	51.0	12 200	12 900	56.5	12 200	13,000	61.0	12 100	12 100
60	46.5	10,300	11 000	53.0	10,300	11 100	57.5	10,400	11 000
65	41.5	8,700	9.400	49.0	8.800	9.500	54.0	8.900	9.600
70	36.0	7,500	8,100	44.5	7,500	8,200	50.5	7,600	8,200
75	29.5	6.400	6.900	40.0	6.500	7.100	47.0	6.500	7.100
80	21.0	5,400	6,000	34.5	5,500	6,100	42.5	5,600	6,200
85		-,	-,	28.5	4,700	5,200	38.5	4,800	5,300
90				20.5	4,000	4,500	33.5	4,100	4,600
95				-			27.5	3,500	3,900
100							20.0	2,900	3,400
MinBm	C			0			6		
Ang Cap	0 (84.5)	2,400	2,400	(94.5)	1,600	1,600	0 (104.5)	900	900







Rated Lifting Capacities In Pounds H Fully Extended Outriggers FULL See Set Up Note 2 Offset 20 Offset 40° Offset Load Radius (Ft.) c エ 360° エ 360° エ 360° 77 0 16,700 30 35 74.5 14,200 40 72.0 13,400 10,500 75.5 45 69.5 12,700 73.0 10,100 76.5 7,900 50 67.0 12,100 70.5 9,600 73.5 7,600 64.5 11.500 68.0 9.100 71.0 7.400 55 60 61.5 10,600 65.0 8,700 68.0 7,200 65 58.5 9,700 62.0 8,300 65.0 7,000 8,400 70 55.0 59.0 8.000 62.0 6.800 75 52.0 7,300 56.0 7,700 58.5 6,700 80 48.5 6,400 52.5 6,800 55.0 6,600 85 44.5 5,500 48.5 5,900 51.0 6,100 90 40.5 4,800 44.0 5,100 46.5 5,300 95 36.0 4,200 39.5 4,400 41.0 4,500 100 31.0 3,600 34.5 3,800 105 25.0 3,200 28.0 3,300 2,700 110 16.5 Min.Bm. 0 700 800 0 900 0 Ang./Cap.

See Set Up Note 2				FU		
Load	2° C	ffset	20°	Offset	40° (Offset
Radius (Ft.)	×°	360°	×°	360°	×°	360°
35	77.0	9,400				
40	75.5	9,400				
45	73.5	9,400	77.0	9,500		
50	71.5	9,400	75.0	9,100	78.0*	7,500
55	69.5	9,200	73.0	8,400	76.0	7,300
60	67.5	8,500	70.5	7,800	73.5	7,100
65	65.0	7,900	68.5	7,300	71.0	6,900
70	62.5	7,300	66.0	6,800	68.5	6,500
75	60.0	6,800	63.5	6,400	66.0	6,100
80	57.5	6,200	61.0	6,000	63.5	5,800
85	54.5	5,300	58.0	5,700	60.5	5,500
90	51.5	4,600	55.0	5,000	57.5	5,200
95	48.5	4,000	52.0	4,300	54.5	4,600
100	45.5	3,500	48.5	3,700	50.5	3,900
105	42.0	3,000	45.0	3,200	47.0	3,300
110	38.0	2,500	41.0	2,700	42.5	2,800
115	34.0	2,100	37.0	2,300		

📣 WARNING

Do Not Lower 28.5 Ft. Offset Fly In Working Position Below 31.5° Main Boom Angle Unless Main Boom Length Is 98 Ft. Or Less, Since Loss Of Stability Will Occur Causing A Tipping Condition.



Rated Lifting Capacities In Pounds Fully Extended Outriggers See Set Up Note 2					FULL	L
Load	2° C	offset	20°	Offset	40° C	Offset
Radius (Ft.)	×°	360°	×°	360°	ێ°	360°
35	78.0*	9,100				
40	76.0	8,600				
45	74.0	8,100				
50	72.0	7,500	78.0*	5,400		
55	70.0	7,000	75.5	5,100		
60	67.5	6,500	73.5	4,800		
65	65.5	6,100	71.5	4,600	77.0	3,600
70	63.0	5,700	69.0	4,400	74.5	3,500
75	61.0	5,400	66.5	4,200	72.0	3,400
80	58.5	5,000	64.0	4,000	69.5	3,300
85	56.0	4,800	61.5	3,800	66.5	3,300
90	53.0	4,500	59.0	3,700	64.0	3,200
95	50.5	4,300	56.0	3,600	61.0	3,100
100	47.5	4,100	53.0	3,500	57.5	3,100
105	44.5	3,700	50.0	3,300	54.0	3,100
110	41.0	3,300	46.5	3,300	50.0	3,000
115	37.0	2,900	43.0	3,200	46.0	3,000
120	33.0	2,500	38.5	2,800	40.5	2,900
125	28.0	2,200	33.0	2,400		
130	22.0	1,900	26.0	2,000		

🕰 WARNING

Do Not Lower 51 Ft. Offset Fly In Working Position Below 15.5° Main Boom Angle Unless Main Boom Length Is 89 Ft. Or Less, Since Loss Of Stability Will Occur Causing A Tipping Condition.



2° Offset

Load	2° 0	ffset	20°	Offset	40° C	Offset
Radius (Ft.)	۲°	360°	۲°	360°	۲°	360°
Rate Fully See	ed Lifting Ca Extended C Set Up Note	pacities In P Dutriggers e 2	ounds		FULL	H
45	77.0	6,200				
50	75.5	6,200				
55	74.0	6,200				
60	72.5	6,200	77.5	4,800		
65	70.5	6,000	75.5	4,600		
70	68.5	5,700	73.5	4,400		
75	66.5	5,300	72.0	4,300	76.5	3,400
80	64.5	4,900	70.0	4,100	74.5	3,400
85	62.5	4,600	68.0	4,000	72.5	3,300
90	60.5	4,300	66.0	3,800	70.0	3,200
95	58.5	4,000	63.5	3,700	68.0	3,200
100	56.0	3,800	61.5	3,500	65.5	3,100
105	53.5	3,500	59.0	3,300	63.0	3,100
110	51.0	3,000	56.5	3,200	60.5	3,000
115	48.5	2,600	54.0	3,000	57.5	2,900
120	45.5	2,200	51.0	2,600	54.5	2,800
125			47.5	2,200	51.0	2,400
130			44.5	1,900	47.0	2,000
		•				

🕰 WARNING

Do Not Lower 51 Ft. Offset Fly In Working Position Below 42.5° Main Boom Angle Unless Main Boom Length Is 89 Ft. Or Less, Since Loss Of Stability Will Occur Causing A Tipping Condition.



WORKING RANGE DIAGRAM





Note: Refer To Page 5 For "Capacity Deductions For Auxiliary Load Handling. Equipment". **X** Loaded Boom Angle In Degrees. () Reference Radius For Minimum Boom Angle Capacities (Shown In Parenthesis) Are In Feet.

On Tire Capacities In Pounds		ON TIRES	<u>Moo ooo</u> o	000000000000000000000000000000000000000
Stationary Capacities Over Front Between T See Operation Note 2	īre Tracks 0	00	MA	IN BOOM "A"
Load	35	Ft.	40	Ft.
Radius (Ft.)	۲°	Load	×°	Load
10	68.0	47,300	70.5	47,100
12	64.0	41,600	67.5	41,400
15	58.5	35,100	62.5	35,000
20	48.0	27,400	54.0	27,300
25	34.5	21,900	43.5	21,700
30			31.0	15,500
Min.Bm. Ang./Cap.	0 (30.0)	15,500	0 (34.5)	11,700
Load	50	Ft.	60.3	Ft.
Radius (Ft.)	×°	Load	×°	Load
15	68.5	34,600		
20	62.5	27,000	68.0	26,800
25	55.5	21,400	62.5	21,200
30	47.5	15,300	56.5	15,100
35	39.0	11,300	50.5	11,100
40	27.5	8,400	43.5	8,300
45			36.0	6,200
50			25.5	4,600
Min.Bm. Ang./Cap.	0 (44.5)	6,400	0 (54.8)	3,300

On Tire Cap Tire Pressur Pick & Carry	acities In Pounds e: See Page 5 / Capacities	S	ON TIRES	s 🖉	<u>///</u>						
Boom Centé See Operati	ered Over Front. on Note 20	(0	0	MAIN BOOM "A"						
Load		35.5 Ft.			40 Ft.						
(Ft.)	చి	Creep	2.5 mph	×°	Creep	2.5 mph					
10	68.0	44,100	38,800	70.5	43,900	38,600					
12	64.0	38,400	33,600	67.5	38,200	33,500					
15	58.5	31,800	27,600	62.5	31,600	27,500					
20	48.0	24,000	20,700	54.0	23,900	20,500					
25	34.5	18,600	15,800	43.5	18,500	15,700					
30				31.0	14,600	12,200					
Min.Bm. Ang./Cap.	0 30.0	14,600	12,200	0 34.5	11,700	9,700					
Load		50 Ft.			60.3 Ft.						
Radius (Ft.)	చి	Creep	mph	×°	Creep	2.5 mph					
15	68.5	31,300	27,200								
20	62.0	23,600	20,300	68.0	23,400	20,100					
25	55.5	18,300	15,500	62.5	18,100	15,300					
30	47.5	14,400	12,100	56.5	14,300	11,900					
35	39.0	11,300	9,400	50.5	11,100	9,300					
40	27.5	8,400	7,300	43.5	8,300	7,200					
45				36.0	6,200	5,500					
50				25.5	4,600	4,100					
Min.Bm. Ang./Cap.	0 44.5	6,400	5,700	0 54.8	3,300	2,900					

/00 MAIN BOOM "B" 50 Ft.

Creep

32,400

24,700

19,500

15,600

12,600

9,700

7,700

2.5

mph

28,300

21,400

16,700

13.200

10,600

8,500

6,900

2.5 mph

17,100

13,700 11,200

9,100

7,400

6,100

4,900

3,900

3,200

									On Tire Ca Tire Press	apacities I ure: See	n Pounds Page 5		ON TIF	RES	20000	100 /	20
On Tire Capacities In Tire Pressure: See F Stationary Capacities	Pounds Page 5			RES	0000 / 0	<u>o /o</u> c	-6	/00	Pick & Car Boom Cer See Opera	ry Capaci itered Ove ition Note	ties er Front. 20	0		0	6> -	MAI	N B
Over Front Between Tire Tracks See Operation Note 20			0	MAIN BOOM "B"				Load		35.5 Ft.	40 Ft					5	
Load 3		35.5 Ft. 40		Ft. 50 Ft.			Radius (Ft.)	×°	Creep	2.5	×°	Creep	2.5 mph	×°	Cr		
Radius (Ft.)	×°	Loa	ad	× ْ	Load	۲°	>	Load	10	68.0	44,100	38,800	70.5	37,900	37,900		
10	68.0	47,3	00	70.5	37,900				12	64.0	38,400	33,600	67.5	37,900	33,900		
12	64.0	41,6	00	67.5	37,900				15	58.5	31,800	27,600	62.5	32,000	27,900	68.5	32.
15	58.5	35,1	00	62.5	35,400	68.5	5	35,800	20	48.0	24,000	20,700	53.5	24,300	21,000	62.0	24.
20	48.0	27,4	00	54.0	27,800	62.0)	28,200	25	34.5	18,600	15,800	43.5	19,000	16,200	55.0	19
25	34.5	21,9	000	43.5	22,300	55.5	5	22,900	30				31.0	15,100	12,700	47.5	15
30				31.0	16,100	47.5	5	16,700	35							38.5	12.
35						38.5	5	12,600	40							27.5	9,1
40						27.5	5	9,700	Min.Bm	0	14 600	12 200	0	12 200	10 200	0	7
Min.Bm. Ang /Cap	0 (30.0)	15,5	600	0 (34.5)	12,200	0 (44.5	5)	7,700	Cap	(30.0)	14,000	12,200	(34.5)	12,200	10,200	(44.5)	7,
J and	(0000)	60	Ft.	-t 70 E		70 F	70 Ft.		Load		0	60 Ft.			70 Ft.		Ft.
Radius	×°	00		Load	×°			Load	(Ft.)		Х̈́	Creep	2.5	mph	۲°	Cre	ер
(FL)	67.5			2000	4	4		Loud	20		67.5	25,000	21	700			
20	67.5		4	20,000	67.0	07.0		22,400			62.0	19,800	16	900	66.5	19,9) 00
20	62.0	-	4	17 100	67.0		23,400		30		56.5	15,900	13	500	62.0	16,1	100
35	50.0			12 000	57.0	62.0 EZ.0		13 100	35		50.0	12,900	10	,900	57.0	13,*	100
40	43.0			12,500	52.0	.0		10,100	40		43.0	10,100	8,	900	52.0	10,3	300
40	35.0			7 900	46.0	16.0		8 200	45		35.0	7,900	7,	200	46.0	8,2	00
45 50	25.0			6 300	40.0			6,200	50		25.0	6,300	5,	800	40.0	6,5	00
55	23.0			0,300	40.0			5,200	55						32.5	5,2	00
60					23.0			4 200	60						23.0	4,2	00
Min.Bm.	0 (54.5)			5,000	0 (64.5)			3,300	Min.Br Ang./Ca	р.	U (54.5)	5,000	4,	700	0 (64.5)	3,3	00



Operation Note 20	U U	ON TIRES	MA	N BOOM "A				
Load	35	.5 Ft.	40	40 Ft.				
Radius (Ft.)	۲°	Load	۲°	Load				
10	68.0	37,200	70.5	36,900				
12	64.0	31,100	67.5	30,900				
15	58.5	24,000	62.5	23,800				
20	48.0	14,500	53.5	14,300				
25	34.5	9,400	43.5	9,300				
30			31.0	6,100				
Min.Bm. Ang./Cap.	0 (30.0)	6,100	0 (34.5)	4,000				
Load	50) Ft.	60.3	3 Ft.				
Radius (Ft.)	×°	Load	x°	Load				
45	00 F	00.400						
15	68.5	23,400	07.5	40.000				
20	62.0	14,000	67.5	13,800				
25	55.0	9,100	62.0	8,900				
30	47.5	5,900	56.5	5,800				
35	38.5	3,800	50.5	3,600				
Ang./Cap.	30.0 (38.9)		45.5 (38.3)					
		WARNIN	G					

					360°		~			. (
On Tire Capacities In Pounds Tire Pressure: See Page 5 Statuonary Capacities_360 Degree											
See Operation I	NOTE 2	0		0	N TIRES			MA	IN BO	DOM "B"	
Load	Load 35.5				40	Ft.		50 Ft.			
Radius (Ft.)	Radius (Ft.) ズ [°]		Load		×°		Load	×°		Load	
10	6	68.0	37,200		70.5		37,400	74.5		37,700	
12	6	64.0	31,100		67.5		31,400	72.5		31,800	
15	ę	58.5	24,000		62.5		24,400	68.5		24,900	
20	4	48.0	14,500		53.5		14,800	62.0		15,400	
25	34.5		9,400		43.5		9,800	55.0		10,300	
30					31.0		6,600	47.5		7,100	
35								38.5		5,000	
40								27.5		3,400	
Min.Bm. Ang./Cap.	0 (30.0)		6,100		0 (34.5)		4,500	10.0 (44.1)			
Load			60 F	٦t.				70	Ft.		
Radius (Ft.)		×°			Load		×°		Load		
20	20		67.0		15,700		71.0				
25	25		62.0		10,700		66.5	5	10,900		
30		56.0			7,500		61.5		7,700		
35		50.0			5,300		57.0		5,500		
40		43.0			3,700		51.5	i i		3,900	
45		35.0			2,500		46.0		2,700		
Min.Bm. Ang./Cap.		33.0 (46.0)				43.5 (47.2	5 2)				
					WARN	11	NG				

Do Not Raise Boom Above 71° Boom Angle. Loss Of Backward Stability Will Occur Causing a Tipping Condition.



